

| DOOR SCHEDULE   |                  |   |       | WINDOW SCHEDULE  |               |              |       |
|---|------------------|---|-------|--|---------------|--------------|-------|
| SYM.  | SIZE             | TYPE  | QUAN. | SYM.   | SIZE          | TYPE         | QUAN. |
| A   | 3'-6" x 8'-0"    | S.C.,R.P., W/ 24" SIDELIGHT W/ SQ. TRANSOM ABOVE  | 1     | 1  | 5'-6" x 7'-6" | ARCHED TOP   | 1     |
| B   | 1 2'-0" x 8'-0"  | SL. GLASS W/ 1 2'-0" x 3'-0" SQ. TRANSOM ABOVE    | 1     | 2  | 5'-6" x 1'-0" | AWNING       | 1     |
| C   | 8'-0" x 6'-8"    | SL. FRENCH DRS. W/ 1 2" SQ. TRANSOM ABOVE         | 1     | 3  | 2'-6" x 5'-0" | PICTURE      | 2     |
| D   | 6'-0" x 6'-8"    | SL. GLASS DRS. W/ 6'-0" x 3'-0" SQ. TRANSOM ABOVE | 1     | 4  | 2'-6" x 1'-0" | AWNING       | 2     |
| E   | 3'-0" x 6'-8"    | SELF CLOSING, M.I.                                | 1     | 5  | 2'-6" x 2'-6" | ARCHED TOP   | 2     |
| F   | PR 2'-6" X 6'-8" | HOLLOW CORE                                       | 2     | 6  | 1'-8" x 4'-6" | ARCHED TOP   | 1     |
| G   | 6'-0" x 6'-8"    | SL. MIRROR  | 1     | 7  | 6'-0" x 4'-6" | HOR. SLIDING | 1     |
| H   | 6'-0" x 6'-8"    | BIFOLD  | 1     | 8  | 5'-0" x 4'-0" | HOR. SLIDING | 1     |
| J   | 4'-0" x 6'-8"    | BIFOLD  | 1     | 9  | 6'-0" x 4'-0" | HOR. SLIDING | 1     |
| K   | PR 2'-0" x 6'-8" | HOLLOW CORE                                       | 1     | 10   | 1'-8" x 4'-6" | CASEMENT     | 2     |
| L   | 2'-8" X 6'-8"    | S.C., M.I.  | 1     | 11   | 3'-6" x 4'-6" | PICTURE      | 1     |
| M   | 2'-8" x 6'-8"    | HOLLOW CORE                                       | 1     | 12   | 4'-0" x 3'-0" | PICTURE      | 1     |
| N   | 2'-6" x 6'-8"    | HOLLOW CORE                                       | 7     | 13   | 3'-6" x 4'-6" | ARCHED TOP   | 1     |
| P   | 2'-4" x 6'-8"    | HOLLOW CORE                                       | 3     | <u>WINDOW NOTES:</u><br>1. ALL WINDOWS TO BE VINYL FRAME, MILGARD OR BETTER<br>2. ALL WINDOWS TO BE U-.40 MIN.<br>3. ALL BEDROOM WINDOWS TO BE WITH IN 40" OF FIN. FLOOR<br>4. GLASS WITHIN 18" OF DOORS TO BE TEMPERED.<br>5. ALL WINDOW HDRS. FOR 8' & 9' CEIL. HEIGHTS TO BE SET AT 6'-8", ALL HDRS FOR 12' CEIL. TO BE SET AT 10'-8", UNLESS OTHERWISE NOTED.<br>6. VERIFY HEIGHT OF WINDOW #7 WITH TUB HEIGHT |               |              |       |
| Q   | 1 6'-0" x 8'-0"  | OVERHEAD, GARAGE                                  | 1     |  |               |              |       |
| R   | 9'-0" x 8'-0"    | OVERHEAD, GARAGE                                  | 1     |  |               |              |       |
| <u>DOOR NOTES:</u><br>1. FRONT DOOR TO BE RATED AT 0.54 OR LESS, VERIFY DOOR STYLE WITH OWNER.<br>2. EXTERIOR DOORS IN HEATED WALLS TO BE U 0.20 OR LESS.<br>3. DOORS THAT EXCEED 50% GLASS ARE TO BE U 0.40 OR LESS.<br>4. ALL GLASS WITHIN 18" OF DOORS TO BE TEMPERED. |                  |   |       |  |               |              |       |

## GENERAL NOTES:

- STRUCTURAL DESIGNS ARE BASED ON 1997 UBC AND 1996 OREGON ENERGY CODE PATH 1.
- ALL PENETRATIONS IN TOP OR BOTTOM PLATES FOR PLUMBING OR ELECTRICAL RUNS TO BE SEALED. SEE ELECTRICAL PLANS FOR ADDITIONAL SPECIFICATIONS.
- PROVIDE 1/2" WATERPROOF GYP. BD. AROUND ALL TUBS, SHOWERS, AND SPAS.
- VENT DRYER AND ALL FANS TO OUTSIDE AIR THRU DAMPERED VENTS.
- INSULATE WATER HEATER TO R-11. PROVIDE 18" HIGH PLATFORM FOR GAS APPLIANCES.
- PROVIDE 1/4" COLD WATER LINE TO REFRIGERATOR.
- BRICK VENEER TO BE PLACED OVER 1" AIR SPACE, AND TYVEK W/ METAL TIES @ 24" O.C. EA. STUD.